









# **INDICATORS IXX STANDARD**

Comparison tech indicators range i xx		i 5	i 20	i 25
DISPLAY	size	33mm	25,4mm	20mm
	Conception	LCD	FSC-LCD	Graphic screen Touch screen
Casing	Plastic	Integrated	NO	NO
	Stainless steel 304 L	NO	Integrated	Integrated
	Size	202*122*92	252*148*58	252*148*58
IP 66		Integrated	Integrated	Integrated
IP69K		NO	Integrated	NO
ATEX	Ex 2-21 IECEx	NO	Ex 2-21 IECEx Or Ex 2-22 IECEx	NO
Power supply 230V/24V		Integrated	Integrated	Integrated
Usage		0,2 A	0,35A	15W

## **INDICATORS IXX STANDARD**

### WE MAKE IT EASY.

INTERFACES		i 5	i 20	i 25
	Analogic measuring	Integrated	Integrated	Integrated
	Digital measuring	NO	NO	NO
	DSD	Integrated (50 000)	Option (300 000)	Integreated (300 000)
	Cable gland number	3	5	5
	Cable gland for communication	1	3	3
	Max number of communication	2*	4	5
	Measuring paths number	1	1	1+1
	∑ of measuring paths	NO	NO	Option
	I/O TOR 2 ins and 4 outs	NON	Option	Option
	Key "Print" in the front	Integrated	Integrated	Integrated
	Print via COM	Integrated	Integrated	Integrated
CONNECTION				
	COM RS 232	Integrated	Integrated	Option
СОМ				
	COM USB	Integrated	Option	Option
	External USB port + USB Key	NO	NO	Option
	External Ethernet port IP54	NO	Option	Option
NEED OF EXTERNAL USB PORT OPTION	USB Barcode reader	NO	NO	Option
	COM RS 232/485	NO	RS232 : Option RS485 : Option	RS232 Integrated RS485 : Option
	ETHERNET (WebServer)	NO	Integrated	Integrated
	DONGLE WIFI	NO	NO	Option
	BLUETOOTH	Option	Option	Option
	Ethernet Modbus TCP / IP	NO	Option Need of option Ethernet IP Link	Option  Need of option Ethernet  IP Link
BATTERY		Option (20h_50h)	Option (18h_48h)	NO
Stainless Steel mounting kit		NO	Option	Option
Mounting kit for compact platform (baseplate)		Option	Option	Option





### WE MAKE IT EASY.

## **INDICATORS IXX STANDARD**

PPLICATIONS		i 5	i 20	i 25
	Counting	Integrated	Integrated	Integrated
	Group couting	NO	Integrated	Integrated
	Controle +/-	NO	Integrated	Integrated
	Controle +/- in counting mode	NO	Integrated	Integrated
	Formulation	NO	Integrated	Integrated
	Controle +/- in formulation mode	NO	NO	Integrated
	Calculation	NO	Integrated (x10)	Integrated
	Animal weighing	Integrated	NO	Integrated
	Tare memory	NO	Integrated (x10)	Integrated (x50)
	HOLD	Integrated	NO	Integrated
	Product sheet	NO	Option (x200)	Integrated(x1000)
	Tare sheets	NO	Option (x50)	Integrated(x50)
	Management of Internal storing CSV	NO	NO	Integrated
	Summation	NO	Option	Integrated
USER NAME	ID 1 / ID 2 (product code)	NO	Integrated	Integrated
BARCODE	Code EAN : 13, 39, 128 etc. (link a code to a product)	NO	NO	Integrated
METROLOGY				
	Sealing kit	Option	NO	Option
LT :	3000e	Integrated	Integrated	Integrated
	2x3000e	Integrated	Integrated	Integrated
	2x6000e	Integrated	Integrated	Integrated
NT :	15000d	Integrated	Integrated	Integrated
	30000d	Integrated	Integrated	Integrated



